

Shrink Packaging Equipment for the Shrinking World

## THE MINI

MAGNET CLAMPING, AUTOMATIC CYCLE TIMING, PIN PERF, TAKEAWAY CONVEYOR



	SI Al	TUNNEL CHAMBER DIMENSIONS						
MODEL	FRONT	X	SIDE	W	X	Н	X	L
TM1319TT (in)	19	Χ	13	12	Χ	6	Χ	20
(cm)	49	Χ	33	36	Χ	16	Χ	51

Sealer and tunnel on a common frame with locking casters and one power source.



## You get more with an EASTEY Built Right ... Priced Right

## **SEALER STANDARD FEATURES**

- Locking 3-inch swivel casters.
- Base with instruction manual.
- Seal head casting equipped with double locking bolts and gas shock head return system.
- Wiring is numbered and color coded

for easy repair and replacement.

Takeaway conveyor.

- Wide product tray has film separation lip for operation ease.
- Film unwind can accommodate up to a 16" wide roll of film.
- Film rack is positioned beneath the infeed frame.
- Product tray and film unwind are connected to minimize product change over time.

## **TUNNEL STANDARD FEATURES**

- Positive Shrinking of all products assured with 4-directional air flow (2 sides, top and bottom).
- Stainless steel mesh conveyor.
- Variable speed conveyor.
- Quiet safe conveyor.

- Variable air flow.
- Sealed bearings not bushings on drive and idler shafts.
- Chain drive powered by an Industrial Gear Motor.
- Solid state temperature controller.

MODEL	MACHINE DIMENSIONS W x H x L			POWER REQUIREMENTS VOLTS PHASE AMPS			WEIGHT		
TM1319TT (in) (cm)	33 84	X X	60 153	X	80 204	110/220 110/220	1	20/15 20/15	1000 lbs. 1000 lbs.

**DEALER IMPRINT** 

EASTEY ENTERPRISES, INC. 21480 147TH AVE. NO., ROGERS, MN 55374 PHONE: 763/428-4846

FAX: 763/428-8361 TOLL FREE: 800/835-9344

www.eastey.com eastey@eastey.com Copyright © 2005 Eastey Enterprises, Inc., All Right Reserved

(Rev. 6/07)